



INTERNATIONAL WATER TREATMENT SPECIALISTS

Tandex Water Filters

Type	Model	Continuous flow rate (lpm)	Peak flow rate (lpm)	Backwash flow rate (lpm)	Valve	Approx. weight (kg)
Multimedia	AFM16	80	108	73	180 or magnum or 172	226
	AFM20	120	160	114	172	320
	AFM24	180	228	180		500
	AFM30	305	384	270	diaphragm	867
	AFM36	430	546	342		1150
Carbon	AFC16	28	38	49	180 or magnum or 172	111
	AFC20	45	60	82	172	137
	AFC24	60	80	114		241
	AFC30	95	125	180	172	409
	AFC36	135	180	270		500
Neutraliser	AFN16	22	30	49	180 or magnum or 172	226
	AFN20	38	49	82		290
	AFN24	53	71	114		474
Birm	AFB16	25	40	49	180 or magnum or 172	152
	AFB20	39	62	82	172	210
	AFB24	57	87	114		338
	AFB30	90	147	180	172	564
	AFB36	135	215	270		705
Manganese Greensand (in continuous regenerated mode)	AFIM16	25	40	49	180 or magnum	206
	AFIM20	39	62	82		300
	AFIM24	57	87	114		464
	AFIM30	90	147	180		762
	AFIM36	135	215	270		975

Filter Range

- **MULTI-MEDIA** - sediment removal down to 10 micron particle size
- **CARBON** - taste, odour, organic colour and chlorine removal
- **NEUTRALISER** - neutralises pH of acidic water
- **BIRM** - iron and manganese removal
- **MANGANESE GREENSAND** - iron, manganese and hydrogen sulphide removal



INTERNATIONAL WATER TREATMENT SPECIALISTS

Tandex Water Filters

Features

- **MEDIA TANKS** - fibreglass outer with ABS or polyethylene liner.
- **VALVE SERIES** - (TOP MOUNT: 180 & MAGNUM SERIES, SIDE MOUNT: 172 & MAGNUM SERIES) 180 series valve, brass body with SS piston. Magnum series and 172 series valves are all plastic construction
- **INTERNAL DISTRIBUTORS** - PVC pipe work and stainless steel screens or all plastic construction laterals/diffuser
- **EXTERNAL PIPEWORK** - class 18 PVC pipe or optional A.B.S.
- **CONTROL OPTIONS** - day timer or remote impulse initiated control. Water meter initiated controls also available
- **MULTIPLE OPTIONS** - all models are available as Multiple systems ie. multiple filters with common manifold allowing for uninterrupted, continuous filtered supply.

